

SAFETY DATA SHEET

BRUSH CLEANER & THINNERS

SECTION 1: Identification of the substance/mixture and of the company/ undertaking 1.1. Product identifier BRUSH CLEANER & THINNERS **Product name** ÷ 1.2. Relevant identified uses of the substance or mixture and uses advised against **Product use** Thinner. t 1.3. Details of the supplier of the safety data sheet ICI Paints AkzoNobel, Wexham Road, Slough, Berkshire, SL2 5DS, U.K. Tel.: +44 (0) 333 222 71 71 www.hammerite.co.uk e-mail address of person : hammerite.advice@akzonobel.com responsible for this SDS 1.4 Emergency telephone number **Telephone number** : Emergency Telephone : Slough +44 (0) 1753 550000 Version : 17.05 3/11/2021 Date of previous issue **SECTION 2: Hazards identification** 2.1 Classification of the substance or mixture **Product definition** : Mixture

 Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

 Flam. Liq. 3, H226

 STOT SE 3, H336

 Asp. Tox. 1, H304

 The product is classified as hazardous according to Regulation (EC) 1272/2008 as amended.

 Ingredients of unknown : 0%

 toxicity

 Ingredients of unknown : 0%

 ecotoxicity

 See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

Hazard pictograms	
Signal word	: Danger
Hazard statements	 H226 - Flammable liquid and vapour. H304 - May be fatal if swallowed and enters airways. H336 - May cause drowsiness or dizziness.
Precautionary statements	
General	 P102 - Keep out of reach of children. P101 - If medical advice is needed, have product container or label at hand.
Prevention	 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P262 - Do not get in eyes, on skin, or on clothing.
Response	 P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. P301 + P310 + P331 - IF SWALLOWED: Immediately call a POISON CENTER or doctor. Do NOT induce vomiting. P312 - Call a POISON CENTER or doctor/physician if you feel unwell.
Storage	: P235 - Keep cool.
Disposal	: P501 - Dispose of contents and container in accordance with all local, regional, national or international regulations.
Hazardous ingredients	: Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics
Supplemental label elements	: Repeated exposure may cause skin dryness or cracking.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	: Not applicable.
Special packaging requirem	ents
Containers to be fitted with child-resistant fastenings	: Yes, applicable.
Tactile warning of danger	: Yes, applicable.
2.3 Other hazards	
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:
Other hazards which do not result in classification	: None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

: Mixture

SECTION 3: Composition/information on ingredients

Product/ingredient name	Identifiers	%	Regulation (EC) No. 1272/2008 [CLP]	Туре
Hydrocarbons, C9-C11, n- alkanes, isoalkanes, cyclics, <2% aromatics	REACH #: 01-2119463258-33	≥90	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304 EUH066	[1]
cyclohexanone	EC: 203-631-1 CAS: 108-94-1	≤10	Flam. Liq. 3, H226 Acute Tox. 4, H332	[1] [2]
n-butyl acetate	EC: 204-658-1 CAS: 123-86-4 Index: 607-025-00-1	≤3	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	[1] [2]
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

<u>Type</u>

[1] Substance classified with a health or environmental hazard

[2] Substance with a workplace exposure limit

[3] Substance meets the criteria for PBT according to Regulation (EC) No. 1907/2006, Annex XIII

[4] Substance meets the criteria for vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

[5] Substance of equivalent concern

[6] Additional disclosure due to company policy

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

General	:	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
Eye contact	:	Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.
Inhalation	:	Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.
Skin contact	:	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.
Ingestion	:	If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

SECTION 4: First aid measures

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

See toxicological information (Section 11)

SECTION 5: Firefighting measures		
5.1 Extinguishing media		
Suitable extinguishing media	: Recommended: alcohol-resistant foam, CO ₂ , powders, water spray.	
Unsuitable extinguishing media	: Do not use water jet.	
5.2 Special hazards arising f	rom the substance or mixture	
Hazards from the substance or mixture	: Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.	
Hazardous combustion products	: Decomposition products may include the following materials: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.	
5.3 Advice for firefighters		
Special protective actions for fire-fighters	: Cool closed containers exposed to fire with water. Do not release runoff from fire to drains or watercourses.	
Special protective equipment for fire-fighters	: Appropriate breathing apparatus may be required.	

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures			
For non-emergency personnel	:	Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.	
For emergency responders	:	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".	
6.2 Environmental precautions	:	Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers, or sewers, inform the appropriate authorities in accordance with local regulations.	
6.3 Methods and material for containment and cleaning up	:	Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Preferably clean with a detergent. Avoid using solvents.	
6.4 Reference to other sections	:	See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.	

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

other sour protected Mixture m from one of Operators conducting Keep awa Avoid con mist arisin sanding. Eating, dr handled, s Put on ap Never use Always ke Comply w Do not alle Informati Vapours a	, the product should only be used in areas from which all naked lights and ces of ignition have been excluded. Electrical equipment should be to the appropriate standard. ay charge electrostatically: always use earthing leads when transferring container to another. should wear antistatic footwear and clothing and floors should be of the g type. y from heat, sparks and flame. No sparking tools should be used. act with skin and eyes. Avoid the inhalation of dust, particulates, spray or g from the application of this mixture. Avoid inhalation of dust from nking and smoking should be prohibited in areas where this material is tored and processed. oropriate personal protective equipment (see Section 8). pressure to empty. Container is not a pressure vessel. ep in containers made from the same material as the original one. th the health and safety at work laws. bw to enter drains or watercourses. on on fire and explosion protection re heavier than air and may spread along floors. Vapours may form mixtures with air.
---	--

7.2 Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations.

Notes on joint storage

Keep away from: oxidising agents, strong alkalis, strong acids.

Additional information on storage conditions

Observe label precautions. Store in a dry, cool and well-ventilated area. Keep away from heat and direct sunlight. Keep away from sources of ignition. No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

7.3 Specific end use(s)	
Recommendations	: Not available.
Industrial sector specific solutions	: Not available.

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Product/ingredient name	Exposure limit values		
cyclohexanone	EH40/2005 WELs (United Kingdom (UK), 12/2011). Absorbed through skin.		
	STEL: 20 ppm 15 minutes. TWA: 10 ppm 8 hours.		
n-butyl acetate	EH40/2005 WELs (United Kingdom (UK), 12/2011). STEL: 966 mg/m ³ 15 minutes. STEL: 200 ppm 15 minutes. TWA: 724 mg/m ³ 8 hours. TWA: 150 ppm 8 hours.		

SECTION 8: Exposure controls/personal protection

Recommended monitoring procedures	:	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
DNELs/DMELs		
No DNELs/DMELs available	e.	
PNECs		
No PNECs available		
8.2 Exposure controls		
Appropriate engineering controls	:	Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the OEL, suitable respiratory protection must be worn.
Individual protection measu	ures	i de la constante de la constan
Hygiene measures	:	Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	1	Use safety eyewear designed to protect against splash of liquids.
Skin protection		
Hand protection		
Gloves	:	When prolonged or frequently repeated contact may occur, a glove with a protection class of 6 (breakthrough time >480 minutes according to EN374) is recommended. Recommended gloves: Viton ® or Nitrile, thickness \geq 0.38 mm. When only brief contact is expected, a glove with protection class of 2 or higher (breakthrough time >30 minutes according to EN374) is recommended. Recommended gloves: Nitrile, thickness \geq 0.12 mm. Gloves should be replaced regularly and if there is any sign of damage to the glove material.
		The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance.
Body protection	:	Personnel should wear antistatic clothing made of natural fibres or of high- temperature-resistant synthetic fibres.
Other skin protection	:	Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	:	If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. OLD LEAD-BASED PAINTS:
		When surfaces are to be prepared for painting, account should be taken of the age of the property and the possibility that lead-pigmented paint might be present. There is a possibility that ingestion or inhalation of scrapings or dust arising from the preparation work could cause health effects. As a working rule you should assume that this will be the case if the age of the property is pre 1960.
		Where possible wet sanding or chemical stripping methods should be used with

SECTION 8: Exposure controls/personal protection

surfaces of this type to avoid the creation of dust. When dry sanding cannot be avoided, and effective local exhaust ventilation is not available, it is recommended that a dust respirator is worn, that is approved for use with lead dusts, and its type selected on the basis of the COSHH assessment, taking into account the Workplace Exposure Limit for lead in air. Furthermore, steps should be taken to ensure containment of the dusts created, and that all practicable measures are taken to clean up thoroughly all deposits of dusts in and around the affected area.

Respiratory protection in case of dust or spray mist formation. (particle filter EN143 type P2) Respiratory protection in case of vapour formation. (half mask with combination filter A2-P2 til concentrations of 0,5 Vol%.)

The current Control of Lead at Work Regulations approved code of practice should be consulted for advice on protective clothing and personal hygiene precautions. Care should also be taken to exclude visitors, members of the household and especially children from the affected area, during the actual work and the subsequent clean up operations. All scrapings, dust, etc. should be disposed of by the professional painting contractor as Hazardous Waste.

Extra precautions will also need to be taken when burning off old lead-based paints because fumes containing lead will be produced. It is recommended that a respirator, approved for use with particulate fumes of lead is selected on the basis of the COSHH assessment, taking into account the Workplace Exposure Limit for lead in air. Similar precautions to those given above about sanding should be taken with reference to protective clothing, disposal of scrapings and dusts, and exclusion of other personnel and especially children from the building during actual work and the subsequent clean up operations.

Avoid the inhalation of dust. Wear suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

Environmental exposure	: Do not allow to enter drains or watercourses.
controls	

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties Appearance Physical state : Liquid. Colour : Various: See label. Odour : Not available. Odour threshold : Not available. Odour threshold : Not available. pH : Not available. Melting point/freezing point : Not available. Initial boiling point and boiling : 149°C range : Flash point : Closed cup: 35°C Evaporation rate : Not available. Upper/lower flammability or : Not available. vapour pressure : Not available. Vapour density : Not available. Relative density : 0,778 Solubility(ies) : Insoluble in the following materials: cold water. Partition coefficient: n-octanol/ : Not available.			
Physical state: Liquid.Colour: Various: See label.Odour: Not available.Odour threshold: Not available.pH: Not available.Melting point/freezing point: Not available.Initial boiling point and boiling range: 149°CFlash point: Closed cup: 35°CEvaporation rate: Not available.Upper/lower flammability or explosive limits: Not available.Vapour pressure: Not available.Vapour density: Not available.Relative density: 0,778Solubility(ies): Insoluble in the following materials: cold water.Partition coefficient: n-octanol/: Not available.	9.1. Information on basic physical and chemical properties		
Colour: Various: See label.Odour: Not available.Odour threshold: Not available.pH: Not available.Melting point/freezing point: Not available.Initial boiling point and boiling range: 149°CFlash point: Closed cup: 35°CEvaporation rate: Not available.Upper/lower flammability or explosive limits: Not available.Vapour pressure: Not available.Vapour density: Not available.Relative density: 0,778Solubility(ies): Insoluble in the following materials: cold water.Partition coefficient: n-octanol/: Not available.	<u>Appearance</u>		
Odour: Not available.Odour threshold: Not available.pH: Not available.Melting point/freezing point: Not available.Initial boiling point and boiling range: 149°CFlash point: Closed cup: 35°CEvaporation rate: Not available.Upper/lower flammability or explosive limits: Not available.Vapour pressure: Not available.Vapour density: Not available.Relative density: 0,778Solubility(ies): Insoluble in the following materials: cold water.Partition coefficient: n-octanol/: Not available.	Physical state	:	Liquid.
Odour threshold: Not available.pH: Not available.Melting point/freezing point: Not available.Initial boiling point and boiling: 149°Crange: Closed cup: 35°CFlash point: Closed cup: 35°CEvaporation rate: Not available.Upper/lower flammability or explosive limits: Not available.Vapour pressure: Not available.Vapour density: Not available.Relative density: 0,778Solubility(ies): Insoluble in the following materials: cold water.Partition coefficient: n-octanol/: Not available.	Colour	:	Various: See label.
pH:Not available.Melting point/freezing point:Not available.Initial boiling point and boiling range:149°CFlash point:Closed cup: 35°CEvaporation rate:Not available.Upper/lower flammability or explosive limits:Not available.Vapour pressure:Not available.Vapour density:Not available.Relative density:0,778Solubility(ies):Insoluble in the following materials: cold water.Partition coefficient: n-octanol/:Not available.	Odour	1	Not available.
Melting point/freezing point: Not available.Initial boiling point and boiling range: 149°CFlash point: Closed cup: 35°CEvaporation rate: Not available.Upper/lower flammability or explosive limits: Not available.Vapour pressure: Not available.Vapour density: Not available.Relative density: 0,778Solubility(ies): Insoluble in the following materials: cold water.Partition coefficient: n-octanol/: Not available.	Odour threshold	1	Not available.
Initial boiling point and boiling range: 149°CFlash point: Closed cup: 35°CEvaporation rate: Not available.Upper/lower flammability or explosive limits: Not available.Vapour pressure: Not available.Vapour density: Not available.Relative density: 0,778Solubility(ies): Insoluble in the following materials: cold water.Partition coefficient: n-octanol/: Not available.	рН	1	Not available.
rangeFlash point: Closed cup: 35°CEvaporation rate: Not available.Upper/lower flammability or explosive limits: Not available.Vapour pressure: Not available.Vapour density: Not available.Relative density: 0,778Solubility(ies): Insoluble in the following materials: cold water.Partition coefficient: n-octanol/: Not available.	Melting point/freezing point	1	Not available.
Evaporation rate: Not available.Upper/lower flammability or explosive limits: Not available.Vapour pressure: Not available.Vapour density: Not available.Relative density: 0,778Solubility(ies): Insoluble in the following materials: cold water.Partition coefficient: n-octanol/: Not available.	•••••••••••••••••••••••••••••••••••••••	1	149°C
Upper/lower flammability or explosive limits: Not available.Vapour pressure: Not available.Vapour density: Not available.Relative density: 0,778Solubility(ies): Insoluble in the following materials: cold water.Partition coefficient: n-octanol/: Not available.	Flash point	1	Closed cup: 35°C
explosive limitsVapour pressure: Not available.Vapour density: Not available.Relative density: 0,778Solubility(ies): Insoluble in the following materials: cold water.Partition coefficient: n-octanol/: Not available.	Evaporation rate	1	Not available.
Vapour density: Not available.Relative density: 0,778Solubility(ies): Insoluble in the following materials: cold water.Partition coefficient: n-octanol/: Not available.		1	Not available.
Relative density: 0,778Solubility(ies): Insoluble in the following materials: cold water.Partition coefficient: n-octanol/: Not available.	Vapour pressure	1	Not available.
Solubility(ies) : Insoluble in the following materials: cold water. Partition coefficient: n-octanol/ : Not available.	Vapour density	1	Not available.
Partition coefficient: n-octanol/ : Not available.	Relative density	1	0,778
	Solubility(ies)	1	Insoluble in the following materials: cold water.
	Partition coefficient: n-octanol/ water	:	Not available.

SECTION 9: Physical and chemical properties

Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Kinematic (room temperature): 0,13 cm ² /s Kinematic (40°C): 0,01 cm ² /s
Explosive properties	: Not available.
Oxidising properties	: Not available.
9.2. Other information	
Solubility in water	: Not available.

SECTION 10: Stability and reactivity

decomposition products	carbon dioxide, smoke, oxides of nitrogen.	
10.6 Hazardous	Decomposition products may include the following materials: carbon monox	kide,
10.5 Incompatible materials	Keep away from the following materials to prevent strong exothermic reaction oxidising agents, strong alkalis, strong acids.	ons:
10.4 Conditions to avoid	When exposed to high temperatures may produce hazardous decompositio products.	n
10.3 Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not or	ccur.
10.2 Chemical stability	Stable under recommended storage and handling conditions (see Section 7	').
10.1 Reactivity	No specific test data related to reactivity available for this product or its ingr	edients.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

There are no data available on the mixture itself. The mixture has been assessed following the conventional method of the CLP Regulation (EC) No 1272/2008 and is classified for toxicological properties accordingly. See Sections 2 and 3 for details.

Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness.

Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the mixture may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin.

If splashed in the eyes, the liquid may cause irritation and reversible damage.

Ingestion may cause nausea, diarrhea and vomiting.

This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
n-butyl acetate	LD50 Dermal	Rabbit	>17600 mg/kg	-
-	LD50 Intraperitoneal	Mouse	1230 mg/kg	-
	LD50 Oral	Guinea pig	4700 mg/kg	-
	LD50 Oral	Mammal -	4300 mg/kg	-
		species		
		unspecified		
	LD50 Oral	Mouse	6 g/kg	-
	LD50 Oral	Rabbit	3200 mg/kg	-
	LD50 Oral	Rat	10768 mg/kg	-
	LD50 Route of exposure	Mammal -	1592 mg/kg	-

SECTION 11: Toxicological information

	unreported LDLo Intramuscular LDLo Intraperitoneal	species unspecified Guinea pig Guinea pig	2648 mg/kg 1500 mg/kg	-	
Conclusion/Summary	Not available.			<u>.</u>	

Acute toxicity estimates

N/A

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
cyclohexanone	Eyes - Severe irritant	Rabbit	-	24 hours 250	-
				Micrograms	
	Eyes - Severe irritant	Rabbit	-	20 milligrams	-
	Skin - Mild irritant	Human	-	48 hours 50	-
				Percent	
	Skin - Mild irritant	Rabbit	-	500	-
				milligrams	
n-butyl acetate	Eyes - Moderate irritant	Rabbit	-	100	-
				milligrams	
	Skin - Moderate irritant	Rabbit	-	24 hours 500	-
				milligrams	
Conclusion/Summary	: Not available.		•	•	•
<u>Sensitisation</u>					

ochoniounon	
Conclusion/Summary	: Not available.
<u>Mutagenicity</u>	
Conclusion/Summary	: Not available.
Carcinogenicity	
Conclusion/Summary	: Not available.
Reproductive toxicity	
Conclusion/Summary	: Not available.
Teratogenicity	
Conclusion/Summary	: Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	Category 3	Not applicable.	Narcotic effects
n-butyl acetate	Category 3	Not applicable.	Narcotic effects

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Product/ingredient name	Result
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	ASPIRATION HAZARD - Category 1

Other information

: Not available.

SECTION 12: Ecological information

12.1 Toxicity

There are no data available on the mixture itself. Do not allow to enter drains or watercourses.

The mixture has been assessed following the summation method of the CLP Regulation (EC) No 1272/2008 and is not classified as hazardous to the environment.

Product/ingredient name	Result	Species	Exposure
cyclohexanone	Acute EC50 32,9 mg/l Fresh water	Algae - Chlamydomonas reinhardtii - Exponential growth phase	72 hours
	Chronic EC10 3,56 mg/l Fresh water	Algae - Chlamydomonas reinhardtii - Exponential growth phase	72 hours
n-butyl acetate	Acute LC50 32 mg/l Marine water Acute LC50 100000 µg/l Fresh water Acute LC50 18000 µg/l Fresh water Acute LC50 185000 µg/l Marine water Acute LC50 62000 µg/l Fresh water	Crustaceans - Artemia salina Fish - Lepomis macrochirus Fish - Pimephales promelas Fish - Menidia beryllina Fish - Danio rerio	48 hours 96 hours 96 hours 96 hours 96 hours

Conclusion/Summary

: Not available.

12.2 Persistence and degradability

Conclusion/Summary : Not available.

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
cyclohexanone	0,86	-	low
n-butyl acetate	2,3		low

12.4 Mobility in soil	
Soil/water partition	: Not available.
coefficient (Koc)	
Mobility	: Not available.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects	: No known significant effects or critical hazards.
----------------------------	---

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment meth	lods
<u>Product</u>	
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non- recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
Hazardous waste	: The classification of the product may meet the criteria for a hazardous waste.

SECTION 13: Disposal considerations

Disposal considerations	Dispose of ac If this product longer apply a	o enter drains or watercourses. cording to all federal, state and local applicable regulations. is mixed with other wastes, the original waste product code may no nd the appropriate code should be assigned. ormation, contact your local waste authority.
Packaging		
Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.	
Disposal considerations	the relevant w Empty contain	tion provided in this safety data sheet, advice should be obtained from aste authority on the classification of empty containers. ers must be scrapped or reconditioned. ntainers contaminated by the product in accordance with local or provisions.
Type of packaging		European waste catalogue (EWC)
CEPE Paint Guidelines	15 01 10*	packaging containing residues of or contaminated by hazardous substances
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapour from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.	

SECTION 14: Transport information

Information pertaining to IATA and ADN is considered not relevant since the material is not packaged in the correct approved packaging required of these methods of transport.

	ADR	IMDG
14.1 UN number	UN1263	UN1263
14.2 UN proper shipping name	PAINT RELATED MATERIAL	PAINT RELATED MATERIAL
14.3 Transport hazard class(es) Class	3	3
Subsidiary class	-	-
14.4 Packing group	III	111
14.5 Environmental hazards Marine pollutant Marine pollutant substances	No.	No. Not available.
14.6 Special precautions for user	Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.	-
Date of issue/Date of	 of revision : 4/30/2021	Page: 11/14

BRUSH	CLEANER	&	THINN	VERS

Information pertaining to IATA and ADN is considered not relevant since the material is not packaged in the correct approved packaging required of these methods of transport.			
HI/Kemler number	30		
Emergency schedules (EmS)		F-E, S-E	
14.7 Transport in bu according to IMO instruments	Ilk : Not applicable.		
Additional information	<u>Tunnel code</u> (D/E)	-	
SECTION 15:	Regulatory information		
	and environmental regulations/legislation spec	ific for the substance or mixture	
	c) No. 1907/2006 (REACH)		
	of substances subject to authorisation		
Annex XIV	nonanta ara liatad, ar the component procent is he	low its threshold	
	ponents are listed, or the component present is be very high concern		
	ponents are listed, or the component present is be	low its threshold.	
Annex XVII - Rest			
on the manufactu			
placing on the ma and use of certai			
dangerous subst			
mixtures and arti	cles		
Other EU regulation			
VOC for Ready-fo Mixture	or-Use : Not applicable.		
	<u>substances (1005/2009/EU)</u>		
Not listed.			
Prior Informed C	Prior Informed Consent (PIC) (649/2012/EU)		
Not listed.			
Seveso Directive This product may add to the calculation for determining whether a site is within the scope of the Seveso Directive on major accident hazards.			
International regulations			
Chemical Weapon Convention List Schedules I, II & III Chemicals Not listed.			
Montreal Protocol			
Not listed.			
Stockholm Convention on Persistent Organic Pollutants Not listed.			
Rotterdam Convention on Prior Informed Consent (PIC) Not listed.			
UNECE Aarhus Protocol on POPs and Heavy Metals Not listed.			

SECTION 15: Regulatory information

15.2 Chemical safety assessment

: No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

CEPE code

Indicates information that has changed from previously issued version.

 ATE = Acute Toxicity Estimate CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008] DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGC = Segregation Group
SGG = Segregation Group vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
STOT SE 3, H336	On basis of test data Calculation method Calculation method

Full text of abbreviated H statements

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.

Full text of classifications [CLP/GHS]

Asp. Tox. 1, H304 EUH066 Flam. Liq. 3, H226	ACUTE TOXICITY (inhalation) - Category 4 ASPIRATION HAZARD - Category 1 Repeated exposure may cause skin dryness or cracking. FLAMMABLE LIQUIDS - Category 3
,	SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (Narcotic effects) - Category 3

Date of printing	: 4/30/2021
Date of issue/ Date of revision	: 4/30/2021
Date of previous issue	: 3/11/2021
Version	: 17.05

Notice to reader

IMPORTANT NOTE The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

SECTION 16: Other information

Brand names mentioned in this data sheet are trademarks of or are licensed to AkzoNobel.

Head Office

AkzoNobel Decorative Coatings BV, Christian Neefestraat 2, 1077 WW Amsterdam, The Netherlands