

**Section 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

**Product name:** LEADMATE PATINATION OIL

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Use of substance / mixture:** PC9a: Coatings and paints, thinners, paint removers.

**1.3. Details of the supplier of the safety data sheet**

**Company name:** EVERBUILD BUILDING PRODUCTS LTD

SITE 41, KNOWSTHORPE WAY

CROSS GREEN INDUSTRIAL ESTATE

LEEDS

WEST YORKSHIRE

LS9OSW

ENGLAND

**Tel:** 0044 113 240 3456

**Fax:** 0044 113 240 0024

**Email:** sds@everbuild.co.uk

**1.4. Emergency telephone number**

**Emergency tel:** 0044 113 240 3456 (office hours only)

**Section 2: Hazards identification****2.1. Classification of the substance or mixture**

**Classification under CHIP:** -: R10; Xn: R40; Xi: R41; Sens.: R43

**Classification under CLP:** STOT RE 1: H372; Carc. 1B: H350; Eye Dam. 1: H318; Flam. Liq. 3: H226; Muta. 1B: H340; Skin Sens. 1: H317

**Most important adverse effects:** Flammable. Limited evidence of a carcinogenic effect. Risk of serious damage to eyes.  
May cause sensitisation by skin contact.

**2.2. Label elements****Label elements under CLP:**

**Hazard statements:** H226: Flammable liquid and vapour.

H340: May cause genetic defects if swallowed.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H350: May cause cancer.

H372: Causes damage to organs through prolonged or repeated exposure.

**Signal words:** Danger

**SAFETY DATA SHEET**  
LEADMATE PATINATION OIL

Page: 2

**Hazard pictograms:** GHS02: Flame  
GHS05: Corrosion  
GHS08: Health hazard



**Precautionary statements:** P102: Keep out of reach of children.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water/shower.  
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+313: IF exposed or concerned: Get medical advice/attention.  
P310: Immediately call a POISON CENTER or doctor.  
P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P233: Keep container tightly closed.  
P243: Take precautionary measures against static discharge.  
P260: Do not breathe vapours/spray.  
P264: Wash hands thoroughly after handling.  
P270: Do not eat, drink or smoke when using this product.  
P272: Contaminated work clothing should not be allowed out of the workplace.  
P321: Specific treatment (see section 4 on this label).  
P370+378: In case of fire: Use carbon dioxide, foam or dry powder for extinction.  
P405: Store locked up.  
P403+235: Store in a well-ventilated place. Keep cool.  
P501: Dispose of contents/container to hazardous waste point.

**Label elements under CHIP:**

**Hazard symbols:** Harmful.



**Risk phrases:** R10: Flammable.  
R40: Limited evidence of a carcinogenic effect.  
R41: Risk of serious damage to eyes.  
R43: May cause sensitisation by skin contact.

**Safety phrases:** S2: Keep out of the reach of children.  
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.  
S46: If swallowed, seek medical advice immediately and show this container or label.

[cont...]

**SAFETY DATA SHEET**  
LEADMATE PATINATION OIL

Page: 3

**2.3. Other hazards**

**Other hazards:** In use, may form flammable / explosive vapour-air mixture.

**PBT:** This product is not identified as a PBT/vPvB substance.

**Section 3: Composition/information on ingredients**

**3.2. Mixtures**

**Hazardous ingredients:**

NAPHTHA (PETROLEUM), HYDRODESULFURIZED HEAVY

EINECS	CAS	CHIP Classification	CLP Classification	Percent
-	64742-82-1	Substance with a Community workplace exposure limit.	Muta. 1B: H340; Carc. 1B: H350; STOT RE 1: H372; Asp. Tox. 1: H304	50-70%

2-BUTANONE OXIME

202-496-6	96-29-7	Xn: R21; Xn: R40; Xi: R41; Sens.: R43	Carc. 2: H351; Acute Tox. 4: H312; Eye Dam. 1: H318; Skin Sens. 1: H317	10-30%
-----------	---------	---------------------------------------	---	--------

**Section 4: First aid measures**

**4.1. Description of first aid measures**

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Consult a doctor.

**Eye contact:** Bathe the eye with running water for 15 minutes. Consult a doctor.

**Ingestion:** Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Get medical attention if there is difficulty breathing.

**4.2. Most important symptoms and effects, both acute and delayed**

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**4.3. Indication of any immediate medical attention and special treatment needed**

**Section 5: Fire-fighting measures**

**5.1. Extinguishing media**

**Extinguishing media:** Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool containers.

[cont...]

**SAFETY DATA SHEET**  
LEADMATE PATINATION OIL

Page: 4

**5.2. Special hazards arising from the substance or mixture**

**Exposure hazards:** Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

**5.3. Advice for fire-fighters**

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes. Collect contaminated fire water separately. Must not be discharged to drains. Dispose of according to local regulations.

**Section 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

**Personal precautions:** Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

**6.2. Environmental precautions**

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

**6.3. Methods and material for containment and cleaning up**

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks. Refer to section 13 of SDS for suitable method of disposal.

**6.4. Reference to other sections**

**Section 7: Handling and storage**

**7.1. Precautions for safe handling**

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is forbidden. Use non-sparking tools.

**7.2. Conditions for safe storage, including any incompatibilities**

**Storage conditions:** Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition. Store in original containers between +5 and +25°C. Storage outside these parameters will dramatically reduce shelf life and invalidates all product warranties.

**Suitable packaging:** Must only be kept in original packaging.

**7.3. Specific end use(s)**

[cont...]

**SAFETY DATA SHEET**  
LEADMATE PATINATION OIL

**Section 8: Exposure controls/personal protection**

**8.1. Control parameters**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	600mg/m3	-	-	-

**Hazardous ingredients:**

**NAPTHA (PETROLEUM), HYDRODESULFERIZED HEAVY**

**Workplace exposure limits:**

**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	600mg/m3	-	-	-

**DNEL/PNEC Values**

**DNEL / PNEC** No data available.

**8.2. Exposure controls**

**Engineering measures:** Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency. Gas/vapour filter, type A: organic vapours (EN141). must be worn if vapour concentration is above OES or if ventilation is poor

**Hand protection:** Impermeable gloves. Change gloves regularly to prevent permeability.

**Eye protection:** Ensure eye bath is to hand. Safety glasses with side-shields.

**Skin protection:** Impermeable protective clothing.

**Section 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

**State:** Liquid

**Colour:** Yellowish

**Odour:** Characteristic odour

**Solubility in water:** Insoluble

**Also soluble in:** Most organic solvents.

**Viscosity:** Non-viscous

**Boiling point/range°C:** 152

**Melting point/range°C:** <-20

**Flash point°C:** 38

**Relative density:** No data available.

**9.2. Other information**

**Other information:** No data available.

# SAFETY DATA SHEET

LEADMATE PATINATION OIL

Page: 6

## Section 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity:** Stable under recommended transport or storage conditions.

### 10.2. Chemical stability

**Chemical stability:** Stable under normal conditions. Stable at room temperature.

### 10.3. Possibility of hazardous reactions

### 10.4. Conditions to avoid

**Conditions to avoid:** Direct sunlight. Hot surfaces. Sources of ignition. Flames. Extremes of temperature.

### 10.5. Incompatible materials

**Materials to avoid:** Strong oxidising agents. Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

**Haz. decomp. products:** In combustion emits toxic fumes.

## Section 11: Toxicological information

### 11.1. Information on toxicological effects

#### Hazardous ingredients:

#### 2-BUTANONE OXIME

ORL	MUS	LD50	1	gm/kg
ORL	RAT	LD50	930	mg/kg
SCU	RAT	LD50	2702	mg/kg

#### Relevant effects for mixture:

Effect	Route	Basis
Irritation	OPT	Hazardous: calculated
Sensitisation	DRM	Hazardous: calculated

### Symptoms / routes of exposure

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be irritation and redness. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

## Section 12: Ecological information

### 12.1. Toxicity

**Ecotoxicity values:** No data available.

[cont...]

**SAFETY DATA SHEET**  
LEADMATE PATINATION OIL

Page: 7

**12.2. Persistence and degradability**

**Persistence and degradability:** No data available.

**12.3. Bioaccumulative potential**

**Bioaccumulative potential:** No data available.

**12.4. Mobility in soil**

**Mobility:** No data available.

**12.5. Results of PBT and vPvB assessment**

**PBT identification:** This product is not identified as a PBT/vPvB substance.

**12.6. Other adverse effects**

**Section 13: Disposal considerations**

**13.1. Waste treatment methods**

**Disposal operations:** Dispose of according to local or national legislation Do not contaminate ponds, waterways or ditches with chemical or used container. Transfer to a suitable container and arrange for collection by specialised disposal company.

**Waste code number:** 08 01 11

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**Section 14: Transport information**

**14.1. UN number**

**UN number:** UN1992

**14.2. UN proper shipping name**

**Shipping name:** FLAMMABLE LIQUID, TOXIC, N.O.S

**14.3. Transport hazard class(es)**

**Transport class:** 3

**14.4. Packing group**

**Packing group:** III

**14.5. Environmental hazards**

**Environmentally hazardous:** No

**Marine pollutant:** No

**14.6. Special precautions for user**

**Section 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

[cont...]

**SAFETY DATA SHEET**  
LEADMATE PATINATION OIL

Page: 8

**15.2. Chemical Safety Assessment**

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

**Section 16: Other information**

**Other information**

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** H226: Flammable liquid and vapour.  
H304: May be fatal if swallowed and enters airways.  
H312: Harmful in contact with skin.  
H317: May cause an allergic skin reaction.  
H318: Causes serious eye damage.  
H340: May cause genetic defects <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.  
H350: May cause cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.  
H351: Suspected of causing cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.  
H372: Causes damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.  
R10: Flammable.  
R21: Harmful in contact with skin.  
R40: Limited evidence of a carcinogenic effect.  
R41: Risk of serious damage to eyes.  
R43: May cause sensitisation by skin contact.

**Legend to abbreviations:** PNEC = predicted no effect level  
DNEL = derived no effect level  
LD50 = median lethal dose  
LC50 = median lethal concentration  
EC50 = median effective concentration  
IC50 = median inhibitory concentration  
dw = dry weight  
bw = body weight  
cc = closed cup  
oc = open cup  
MUS = mouse

[cont...]



**SAFETY DATA SHEET**  
LEADMATE PATINATION OIL

Page: 9

GPG = guinea pig  
RBT = rabbit  
HAM = hamster  
HMN = human  
MAM = mammal  
PGN = pigeon  
IVN = intravenous  
SCU = subcutaneous  
SKN = skin  
DRM = dermal  
OCC = ocular/corneal  
PCP = physico-chemical properties

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.